

Customer: _____ Date: _____

Tag Number: _____ Name: _____

ELECTRONICS:

- 4700 (2 Path) 4700 (3 Path)
- Heater Modem Chart Recorder Relays (5max)_____ Keylock

SENSORS:

- Strap On Hotshot Internal Wetted Windowed (spool)
- Cable length: Standard 50ft 100ft Other: _____ ft. Splices not recommended

Special Sensor requirements (eg. Tapping saddles, mounting hoops, etc.):

- Spool Piece required? Yes No
- Flange: AWWA CI D ANSI RF Other: _____
- Flange Material: Standard Carbon Steel Other: _____
- Spool Body Material: Standard Other: _____
- Spool Laying Length: Standard Other: _____ inches
- FM hazardous location required? Yes No

PIPE INFORMATION:

- Pipe Size: _____ inches
- Pipe Material: Carbon Steel PVC Stainless Steel Cast Iron Ductile Iron
- RCP RCCP Other: _____
- Pipe O.D. _____ inches. Pipe I.D. _____ inches. Pipe Wall Thickness: _____ inches.
- Pipe liner: Yes No Liner Material: _____
- Liner Thickness: _____ inches

FLOW INFORMATION:

- Maximum Flow Rate: _____ GPM GPD MGD CFS CFM CFD M3H
- M3S MLD M3D LPM LPS MGD LPD Imperial GPM BPH
- Flow Direction: Uni Bi
- Totalizer: Forward Forward & Reverse Differential
- Totalizer Units: GAL CuFT Acre Ft Imp Gal M3 Liters Barrels
- Totalizer Multiplier: X

FLUID:

- Water Wastewater Other: _____ Specific Gravity: _____ Viscosity: _____ cp Sonic
- V: _____
- Fluid Temperature: Max _____ degrees F, Norm. _____ degrees F, Max Pressure _____ psi.
- Solids: Yes No Type of Solids: _____ Percent Solids in Fluid: _____ %
- Upstream Straight run: _____ Ft. From: Tee/elbow Valve Pump Other:
- Downstream Straight run: _____ Ft.

NOTE: PLEASE SUBMIT DRAWINGS OF UPSTREAM AND DOWNSTREAM PIPING